

**CANARA BANK**

**PROPOSED INTERIOR FURNISHING WORK OF BRANCH-II AT RAMGANJMANDI**

| S.NO.    | DESCRIPTION  | UNIT | QNTY | RATE | AMOUNT |
|----------|--|------|------|------|--------|
|          | i) The work to include all demolishen and diposal, shifting etc. as required, no extra   |      |      |      |        |
|          | ii) The work to include shifting / reshifting etc. (including wiring arrangements) as required to be done , on day to day basis, for branch functioning, no extra payment will be given for this item  |      |      |      |        |
|          | iii) The plywood must be treated with Anti-termite Solution before application.  |      |      |      |        |
| <b>1</b> | <b>GYPSUM FALSE CEILING</b>  | S.FT | 350  |      |        |
|          | A) P&F false ceiling with Gypsum Board 12.5mm thick fixed to a metal frame comprised of ceiling channel of size 80mm X 26mm X 0.5mm @ every 450 cms centres, inter channel 45mm X 15mm X 0.9mm @ every 1220mm centres, peri-meter channel 20mm X 26mm all along the wall, strap hanger suspendeds 25mm X 0 5mm with nuts and bolts 6.4mm x 12.7mm, connecting clip 2.64mm thick, dry walls screw 25mm long , soffit cleat. 27mm X 37mm X 25mm X 1.6mm thick and dash fasterner/ rawl plug 12.5mm dia X 35mm long with 6mm dia bolt. The joint of gypsum board to be taped 3 times and sealed with jointed compound with three coat plastic emulsion paint finished. Cut-out are provided to accommodate luminaries, air conditioning grills and fire warming dectors if any. |      |      |      |        |
|          | The rate to include two or more coats of approved paint after preparing the surface. All fitting to be separately hung from the ceiling and should not rest on the false ceiling.  |      |      |      |        |
| <b>2</b> | <b>GRID FALSE CEILING</b>  | S.FT | 800  |      |        |
|          | The grid false ceiling shall be provided in the Banking Hall, Manager's etc. The ceiling height and level shall be determined at the perimeter. The minimum height of the ceiling cavity should be 100mm. All service fittings integrated within the suspended ceiling must be independently supported from the ceiling grid by a structure designed for the purpose.  |      |      |      |        |
|          | <input type="checkbox"/> <b>Ceiling tiles</b>  |      |      |      |        |
|          | Shall be Armstrong Fine fissured Classic lite RH99 of 16mm thickness. Suspension system Shall be of Armstrong Trulok Silhouette reveal profile grid system with 15mm flanges incorporating 3mm central recess in global white with black reveal. Silhouette main runners and cross tees to have mitred ends and "birdsmouth" notches to provide mitred cruciform junctions.  |      |      |      |        |

|          |   |     |        |  |  |
|----------|---|-----|--------|--|--|
|          | <b>◆ Installation</b>   |     |        |  |  |
|          | Main runners will be placed at 1200mm centers securely fixed to the structural soffit by approved hangers at 1200mm maximum centers and not more than 150mm from spliced joints. The last runner at the end of each main runner should not be greater than 600mm from the adjacent wall. 1200mm long cross tees to be interlock between main runners at 600mm centers to form 1200x600mm modules. Cross tees longer than 600mm require independent support. 600x600mm modules to be formed by fitting 600mm long cross tees centrally between the 1200mm cross tees. The 1200mm cross tees to have central "birdsmouth" notches to facilitate fitting of 600mm cross tees. The perimeter trim to be Armstrong Trulok equal wall angle of white color secured to walls at 450mm maximum centers.   |     |        |  |  |
| <b>3</b> | <b>FULL HEIGHT PARTITION</b>  |     |        |  |  |
|          | Providing Fabricating & Fixing of partition made out with ALLUMINIUM RECTANGULAR RT consisting of 2"x1" section placed at min 2'-0"x2'-0" horizontally & vertically (as per site requirement ) with 12mm WATERPROOF MDF finished with 1mm thick high gloss laminates ( of approved shade ) on both sides (as approved) . The sides /top shall be finished with teak wood beading (3" x 1") with high gloss Melamine Polish .This partition will be upto false ceiling level with framing section screwed to rcc slab, walls and floor in chemical grout as per approved design .Providing 12mm toughened clear glass with Frosted Film . Glass fixed with Teak wood beading with pu finish ,grooving pattern as per design.including all necessary required hardware and fitting as per approved by architect /engineer incharge. Partition as above in sqft. (top width including partition glass & ht. will be measured for payment ) | SFT | 270.00 |  |  |
| <b>4</b> | <b>LOW HEIGHT PARTITION</b>   |     |        |  |  |
|          | Providing & fabricating & fixing of low height partition made out with ALLUMINIUM RECTANGULAR RT framework consisting of 2"× 1" sections placed at minimum 2'-0" × 2'-0" horizontal & vertical (as per site requirement) with 12mm WATERPROOF MDF with 1 mm thick laminate (of approved shade) on both sides (as approved). Partition will be 4'-0 high (as per design) with 8 mm thick toughened glass clear including frosting /etching as per design fixed with T.W beading with Melamine Polish.  | SFT | 130    |  |  |
|          | 8 mm toughened glass will be supported by box pillar made out of 12 mm commercial ply with support of ALLUMINIUM RECTANGULAR RT Section.Top edge of 8mm toughened glass will be with diamond cut & diamond edge polish includes making required cut out. including all necessary required hardware ,fitting as per approved by architect/engineer in charge.  |     |        |  |  |

|          |   |        |        |  |  |
|----------|---|--------|--------|--|--|
| <b>5</b> | <b>PANELLING WORK</b>   |        |        |  |  |
|          | <b>Wall panelling WITH LAMINATE</b>   |        |        |  |  |
|          | Providing & Fixing of WALL panelling made out with ALLUMINIUM RECTANGULAR RT Sections consisting of 2" x 1" section placed at min. 2'-0"x2'-0" horizontally & vertically (as per site requirement) with 12mm Waterproof MDF Board (make Archidply, Century, Greenply, Kitply) finished with 1mm thick laminates of approved shade and Make ( Archidply, Century, Greenply, Merino, Sunmica,Austin ) over the wall as per approved drawings. The rates are including the design provided in the approved drawing this panelling will be upto false ceiling level with framing section screwed to rcc slab, walls and floor in chemical grout as per approved design grooving pattern as per design.including all necessary required hardware ,fitting as per approved by Architect/ Bank incharge. | SFT    | 360.00 |  |  |
| <b>5</b> | <b>TOUGHENED GLASS</b>  |        |        |  |  |
| <b>a</b> | <b>DOOR</b>   |        |        |  |  |
|          | 12 MM TH. TOUGHENED GLASS Cabin door providing & fixing main doors/cabin made out of/cabin door made out of HNG/ Asahi India MAKE 12 MM TH.toughened glass Frosting film / etching as per design in single piece with computerised diamond cut & diamond edge polish including making required cutout holes for lock , handles , pivot patch fitting , corner fitting hinges etc. the rate is inclusive of patch fitting of dorma make floor spring ,pivot patch fitting with cover plate locks handles , singsges with necessary hardware rtc. as per intructions of Architect/Engineer.   | SFT    | 65     |  |  |
| <b>b</b> | <b>FIXED</b>  | Sq.ft. | 20     |  |  |
| <b>6</b> | <b>ENAMEL PAINT</b>   |        |        |  |  |
|          | Providing & laying 2 or more coats of Syntheic Enamel paint for exissting grill & railing & flooring as per instructions  | SFT    | 320.00 |  |  |
| <b>7</b> | <b>PIN BOARD</b>  |        |        |  |  |
|          | Providing and fixing pinup boards. It consist 12mm thick soft boards of good density to be mounted over 12mm thick comm. ply. The soft board will be covered with a plain fabric (appox Rs.250 /Rmts. of approved colour) from front and edges. Suitable steam beach moulding 25mm x 25mm size to be fixed on all four sides and will be finished in melamine polish.   | Sq.Ft. | 30     |  |  |
| <b>8</b> | <b>A.C.P. PANELLING (External 4 mm)</b>   |        |        |  |  |
|          | Proving and fixing in position Aluminium composite panel Boxing with PVDF coating & LDPE core laminated Eurobond / Altobond/ Alukbond Exterior Grade 4 mm thick with composite of (0.5mm - 3mm- 0.5mm) including fabrication for the same with aluminium sections, required hardware, silicon sealent (Dow Corning 789) masking tape, necessary scaffolding etc. complete in all respects.  | Sq.Ft. | 100    |  |  |

|          |  |       |     |  |  |
|----------|--|-------|-----|--|--|
| 9        | <b>FLUSH DOOR WITH DOOR CLOSURE</b>  |       |     |  |  |
|          | Providing & Fixing 30mm solid core flush door of approved make as per instruction of Engineer in- Charge complete with door closure of Godrej/ Dorma/ Ozone of two speed ( heavy duty , light weight thin. Type code : 3976) as approved by etc.   | Sq.ft | 21  |  |  |
| 10       | <b>KEY BOX</b>   | NOS.  | 1   |  |  |
| 11       | <b>STORAGE CABINET</b>   |       |     |  |  |
|          | <b>Low height &amp; Full Height</b>  |       |     |  |  |
|          | Providing & fixing low height storage cabinet 1'-4" deep in 19mm thick commercial board with box type cabinet  | SFT   | 120 |  |  |
| 12       | <b>TABLE AND COUNTERS</b>  |       |     |  |  |
| <b>A</b> | <b>BM TABLE WITH SIDE UNIT</b>   | NOS.  | 1   |  |  |
|          | Supplying & fixing –BM Table 6'-0"× 3'-0"×2'-6" made out of 19 mm BWR board with 1 mm thick laminate as  |       |     |  |  |
| <b>B</b> | <b>RUNNING COUNTER</b>   | R.ft. | 20  |  |  |
|          | Providing & fixing in position public counters as per approved design 750 mm high and 750 mm wide made with 19 mm thick comm. Board finished with 1.0 mm thick laminate as per desired shade and design on all exposed surfaces expect top, which is finished with and other exposed edges polished for with following provisions. complete in all respects as per Bank Engineer/ Architect.<br>a) Keyboard tray made with 19 mm comm. Board with 1.00 mm laminate on top & steam beach front on telescopic channels with locking arrangement. Complete in all respect.<br>b) A platform to be made inside table for CPU of 19 mm comm. Board with 1.0 mm laminate on top and teak wood footrest of size 3" X 1½". |       |     |  |  |
|          | c) A necessary hole to be made on table top for cable manager with plastic wire box.<br>d) A drawer unit is to be made from 12 mm thick teak wood members side with 19 mm thick facia of comm. Board with 1.0 mm thick laminate top. One drawer to run on telescopic channels with auto lock / multipurpose locks etc.<br>e) All internal surfaces to be provided with .8mm thk laminate of desired shade.<br>f) All exposed edges to be provided with stream beach wood moulding. Complete as per design. The rates are inclusive of 10mm Glass on Top with provision for wire manager.   |       |     |  |  |
| <b>C</b> | <b>CASH COUNTER</b>  | R.ft. | 5   |  |  |
|          | Providing and erection in position Cash Counters /Cash work Station of approx. Size 1200 X 900 X 750 mm inclusive of 1100 mm high, 350 mm wide customer writing top finished with laminate of approved shade.<br><br>The cash counters shall be made of 19 mm thick BWR grade block board finished with 1.00 mm thick Laminate sheet including inner faces. Free edges shall have Rubber wood mouldings of half-round profile as per drawings and instructions, Inner face of modesty panel and free sides are to be clad with 16 gauge M. S. sheet, painted with two coats of synthetic enamel paint of approved shade and brand over a coat of approved steel primer.  |       |     |  |  |

|                                  |   |     |    |  |  |
|----------------------------------|---|-----|----|--|--|
|                                  | <p>Each cash work station shall comprise of the following ;<br/> Drawer unit made with 12 mm thick ply on 3 sides &amp; on bottom the front will be in 19 mm th block board<br/> Cash drawers having slots for keeping cash of different denominations with approved telescopic channels for drawer-sides, automatic locks (keys in duplicate) and other necessary hardware and accessories including satin finish S. S. handles of approved quality ;<br/> Readymade keyboard drawer of engineering plastic (KD 575 PMT/INNOFIT SYSTEMS OR Equivalent approved make) and all necessary accessories, suitably suspended below table top.<br/> The front of the cash counters shall have 12 mm thick toughned glass in two pieces at sides with polished Rubber wood glazing beads as per instructions and drawings.</p> |     |    |  |  |
| 13                               | <p><b>SLIPS COUNTER / WRITING LEDGE</b> :10 mm bevelled clear glass to SLIP counter 3'0" x 1'3" x 3'6" height with shelf and Pigeon holes to keep slips 19mm block board fabrication approved pattern laminated as per design in drawing with divisions below and shutter in front to create to boxes for mail, cleaning etc. with suggestion box made out of solid ply and finished with 1 mm thk laminate. 1" high slit is to be made in the front for letter and cheque box, 0.8 mm thick white Laminate on the inside 1" thk slit to be made in the front for letter / cheque etc. the work should be as per direction .</p>  | Nos | 1  |  |  |
| 14                               | <p><b>Shutter boxing with trap door:</b> Providing &amp; fixing in position Aluminium Composite Panel (ACP) with framing of Aluminium Tube sections of min 1.5" x 1" and 20 gauge 2'-0" C/C both ways. Mirror screws to be used. Joints to be finished with Silicon based sealant. ACP thickness of 3 mm minimum. Aluminium foil thickness to be min 0.20 mm., 2'-0" C/C both ways. ACP to be in 2' width panels or distributed equally. Alubond, Eurobond, Fujibond, Alcobond or equivalent ISO certified brands to be used. Shades to be as per bank's approval. Trap door will be made out of 6 mm water proof ply finished with ACP.</p>  | Sft | 70 |  |  |
| <b>TOTAL FOR FURNISHING WORK</b> |   |     |    |  |  |